

3M**Scotchshield™****Ultra Safety and Security Window Film**

SCLARL400

**Inside View****Ultra 400 Series****Product Benefits**

- Reduces fading from UV light, furniture and fabrics have a longer acceptable life.
- Increases personal safety from flying glass.
- Deters smash and grab burglaries.

Performance Data

With SCLARL400	1/4" Single Clear	1/4" Single Tinted	Insulated Clear	Insulated Tinted
Solar Heat Reduction	3%	1%	2%	0%
Heat Loss Reduction	0%	0%	0%	0%
Glare Reduction	2%	4%	0%	7%
UV Blocked	98%	99%	99%	99%

Technical Data

Glass Type	Applied Product	Shading Coefficient	Visible Light		Emissivity	"U" Value
			Reflection	Transmitted		
1/4" Single Clear	None	0.94	8%	88%	0.84	1.06
	SCLARL400	0.91	11%	86%	0.87	1.06
1/4" Single Tinted	None	0.69	5%	50%	0.84	1.06
	SCLARL400	0.68	6%	48%	0.87	1.06
Insulated Clear	None	0.81	14%	78%	0.84	0.50
	SCLARL400	0.79	18%	75%	0.87	0.50
Insulated Tinted	None	0.55	8%	45%	0.84	0.50
	SCLARL400	0.55	8%	42%	0.87	0.50

Meets Safety Glazing Standard **CPSC 16 CFR** Category II (400 ft./lb.) and **ANSI Z97.1**, and passes Intensified Weathering Test.

LDT AB

Odensalatvätten
195 92 Märsta
Tel: 08-653 76 00 Fax: 08-645 30 00
e-post: ldtab@ldtab.com
websida: www.ldtab.com

Printed in U.S.A.

© 3M 2004 70-0703-7196-1 (642.5)ii

3M Consumer Safety and Light Management

3M Center, Building 223-2S-24
St. Paul, MN 55144-1000
Phone: 800-480-1704
Fax: 651-736-0611
www.3M.com/windowfilm